

Spectralink DECT Server 8000

Modular and Customizable DECT Wireless Telephony for Medium to Large Enterprises



BENEFITS

- Seamless migration from analog to SIP VoIP telephony
- Dramatically improves responsiveness and productivity of mobile workers
- Increases business efficiency by integrating with application systems and business processes
- Reduces the number of on-site service visits via service facilities such as management reports and analyzing tools
- Low power consumption fosters a greener environment and reduces costs
- Rack and wall mountable, indoor
- Ability to mix digital and IP base stations in one system
- Allows for synchronization via air or LAN (Local Area Network)

The Spectralink DECT Server 8000 is a modular, scalable and flexible wireless mobility solution with combined analog and SIP VoIP interface that can be customized to exactly match your wireless telephony needs today and in the future. With its ability to easily scale, it fits the needs of medium to large-sized enterprise businesses.

The Spectralink DECT Server 8000 solution can be customized to specific wireless needs via a number of optional interface cards: a CPU card with or without link option, a base station card that connects up to eight Spectralink DECT Base Stations, an analog card with eight or 16 lines, and the SIP VoIP card that acts as a media resource card for 32 VoIP connections. You can also connect up to 1,024 Spectralink IP-DECT Base Stations.

Each Spectralink DECT Server 8000 has room for one CPU card and up to eight interface cards. Further, up to eight servers can be linked together. With a combined total of 64 slots, the Spectralink DECT Server 8000 solution allows for numerous ways to deploy a wireless mobility solution that matches the exact telephony needs of your organization.

Businesses that need radio coverage over a large geographical area, with multiple locations, or a large number of mobile employees can benefit from the Spectralink DECT Server 8000 solution, which supports up to 4,095 wireless users and 1,024 simultaneous calls.

The extremely scalable and flexible nature of the Spectralink DECT Server 8000 solution makes it an ideal add-on solution for fast-growing and large businesses since the solution can be expanded as the business grows.

SPECIFICATIONS

DIGITAL LINE SUPPORT

- CLIP FSK Bell core
- DTMF CLIP
- Loop break
- DTMF transmit
- Dial and busy tone detect

SIP VOIP SUPPORT

- Basis call
- CLIP
- Call Hold
- Call Transfer

PROTOCOL SUPPORT

- Broadcast Messaging
- Message Service Functions (MSF)
- Telocator Alphanumeric Protocol 1.8 (TAP)
- XML-RPC

SYSTEM ARCHITECTURE

- Stable system core based on Linux
- Faster access to standard protocols
- CPU card without link option has build-in Media Resource for 8 Channels
- Max. no. of:
 - Registered Spectralink handsets: 4,095
 - Simultaneous calls: 1,024
 - Simultaneous calls per media resource (G.711 & G. 726): 32
 - Spectralink DECT Base Stations: 512
 - Spectralink DECT Repeaters: 3 per Base Station
 - Spectralink IP-DECT Base Stations: 1,024 (takes up two channels on the media resource card)
 - Linked servers: 8
 - Interface cards in one linked system: 64

SUPPORTED CODECS

- G.711 A-law and μ -law
- G.726 (32kbps - 4 bit ADPCM)

APPROVALS (REGULATORY STANDARDS)


- EN55022: Class A
- EN55024: A1, A2
- CRF47, PART15, Subpart B
- CISPR 22
- ICES-003
- CAN/CSA-CEI/IEC CISPR 22

SAFETY (REGULATORY STANDARDS)

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- UL File No: E170690
- IEC 60950-1
- EN60950-1
- AS/NZS 60950-1

Note: For latest approvals and regulatory compliance, please check our website.

Spectralink DECT Server 8000 Configuration



ENVIRONMENTAL CONDITIONS

- Operating temperature: 32° - 104° F (0 - 40° C)
- Storage temperature: -22° - 158° F (-30° - 70° C)
- Relative humidity: between 20% and 80% (non-condensing)
- Operating altitude: Up to 9,483 ft. (3,000 m.)
- The equipment is compliant with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

ELECTRICAL REQUIREMENTS

- Power adaptor characteristics: De 19 VDC /9.48 A
- The supplied power for AC adaptor power supply must be 110 – 240 VAC nominal, 50/60 Hz

PHYSICAL CHARACTERISTICS

- Size: 7 x 17 x 13 in. (177 x 422 x 328 mm)
- Weight: 11.8 lb (5.34 kg) excl. power supply
- Up to 26.5 lb (12 kg) incl. adapters
- The shelf is four units high in rack

INTEROPERABILITY

- For information about supported Call Control / Unified Communications (UC) (PBX and IP-PBX) platforms, visit support.spectralink.com.

About Spectralink

Spectralink delivers secure, cost-effective mobile communication solutions that empower enterprises to streamline operations, increase their revenues and deliver a positive customer experience – each and every time. Since 1990, Spectralink has deployed millions of devices worldwide across the retail, healthcare, hospitality and manufacturing sectors – providing workers with the industry's most efficient, in-building communications.

For more information, visit spectralink.com or call 303.441.7500.



spectralink.com
info@spectralink.com
+1 800-775-5330 North America
+45 7560 2850 EMEA

©2016 Spectralink Corporation. All rights reserved. (12/16)